SAFETY DATA SHEET



1. INDENTIFICATION OF SUBSTANCES / PREPARATION AND COMPANY

Product Name: Product Code:	Enigma Colour Tone Liquid 0356, 0359, 0673
Application:	Liquid carrier medium for acrylic polymer powder
Company:	Davis Schottlander & Davis Ltd Fifth Avenue, Letchworth Garden City, Herts SG6 2WD UK Tel: +44 (0)1462 480848 Fax: +44 (0)1462 482802 msds@schottlander.co.uk www.schottlander.com
Date:	24.11.2015 V3.0

2. HAZARD IDENTIFICATION

Classification of the substance or mixture

This substance is classified as hazardous according to GHS. <u>Regulation EC1272/2008</u>

Physical Health	H225 H315 H317 H335	Irritatio Skin sei Specifio	able Liquids on of skin nsitisation c Target Organ Toxicity - exposure (inhalation)	Hazard catego Hazard catego Hazard catego Hazard catego	ory 2 ory 1B
Label elements			000		
In Accordance with Regu	lation EC				
Signal word		Danger	· •		~
GHS Pictogram					
			H315 H317 H335		H225
Hazard Statement	H225		Highly flammable liquid	l or vapour	
	H315		Causes skin irritation	·	
	H317		May cause an allergic s	kin reaction	
	H335		May cause respiratory i	rritation	
Precautionary Statement	t				
(Prevention)	P210		Keep away from heat/s	parks/open	
. ,			flames/hot surfaces. No	smoking.	
	P261		Avoid breathing dust/fu	ume/gas/mist/v	vapours/spray
	P280		Wear protective gloves/protective clothing/eye protection/face protection		thing/eye
(Response)	P303+3	361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.		





(Disposal)

P501

Dispose of contents/container in accordance with local regulation

Hazardous components for labelling:

Methyl methacrylate

Other hazards:

Polymerisation with heat evolution may occur in the presence of radical forming substances (e.g peroxides), reducing substances, and/or heavy metal ions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substances

In accordance with Regulation EC 1272/2008

Component	CAS No.	Content	Hazard/category/statement
	EC Index No.		
	REACH No.		
	EINECS No.		
Methyl Methacrylate	80-62-6		Flam. Liq./2/H225
	607-035-00-6		Skin Irrit./2/H315
	01-2119452498-28		Skin Sens./1/H317
	201-29701		STOT SE (inhalation)/3/H335
Ethylene Glycol	97-90-5		Skin Sens./1/H317
Dimethacrylate	607-114-00-5		STOT SE (inhalation)/3/H335
	Pre-registered 202-617-2		

4. FIRST AID MEASURES

Description of first aid measures

General advice	Medical treatment is necessary if symptoms occur which are obviously caused by skin or eye contact with the product, or by vapour inhalation. Remove soiled soaked clothing immediately.
Inhalation	Move casualty to fresh air and keep them calm. Seek medical attention.
Skin contact	Wash off immediately with soap and water. If skin irritation occurs, seek medical attention.
Eye contact	Holding eyelids open, immediately rinse thoroughly with plenty of water. Seek medical advice.
Ingestion	Do not induce vomiting. Immediately contact a doctor.

Most important symptoms and effects, both acute and delayed

Causes skin and eye irritation. Skin sensitisation.

5. FIRE FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Foam, dry powder, carbon dioxide Unsuitable extinguishing media: Water





Special hazards arising from the substance or mixture: No

Advice for fire fighters: Wear self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective clothing. Keep away from sources of ignition. Use breathing apparatus if exposed to vapour/dust/mist/aerosol.

Environmental procedures

Do not allow to enter drains/surface water/ground water/sewerage systems. If entry occurs IMMEDIATELY alert The Environment Agency or other equivalent appropriate body.

Methods and material for containment and cleaning up

Larger volumes: remove mechanically (by pumping). Use explosion-proof equipment. Smaller volumes and/or residues: contain with absorbent material (eg. sand, diatomaceous earth, acid absorbent, universal absorbent or sawdust). Dispose of in accordance with local regulations.

Reference to other sections

For personal protection see section 8. For disposal considerations see section 13.

7. HANDLING AND STORAGE

Precautions for safe handling

Ensure the area is well ventilated. Keep container tightly closed. Keep away from heat, sparks and open flame – no smoking. Take precautionary measures against static discharge. In the event of fire, use explosion-proof equipment only. Cool the endangered containers with water. When heated above the flashpoint and/or during spraying (atomising), ignitable mixtures may form in air.

Conditions of safe storage, including any incompatibilities

Keep only in the original container and do not allow temperature to exceed 30°C. Protect from light. Fill the container by approx. 90% only as oxygen (air) is required for stabilisation. With large storage containers, ensure oxygen supply is sufficient to allow stability. Can polymerise with intense heat release.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters:

Components or products of decomposition according to point 10, with limit values related to the place of work which require monitoring.

Methyl Methacrylate	CAS No. 80-62	2-6
WEL (8hrs)	208mg/m ³	50 ppm
WEL (15mins)	416 mg/m^3	100 ppm





Exposure controls:

Derived No-Effect Level (DNEL)

Critical Component	Routes of Exposure (LONG- TERM)	DNEL
Methyl Methacrylate	Inhalation	210mg/m ³
	Dermal	74.3mg/m ³
	Oral	-

Predicted No-Effect Concentration (PNEC)

Critical Component	Routes of Exposure (LONG- TERM)	PNEC
Methyl Methacrylate	Water	0.94mg/l
	Soil	-
	Air	-

General protective measures: Do not inhale vapours. Avoid contact with eyes and skin.

Personal Protective Equipment:



Hygiene measures:	Store work clothes separately. Remove soiled or soaked clothing immediately. Follow the usual good standards of occupational hygiene. Clean skin thoroughly after handling. Apply skin cream.
Respiratory protection:	If ventilation is insufficient, breathing apparatus to be used in case of high concentrations, short term: filter appliance, filter A.
Hand protection:	Butyl rubber gloves (0.7mm), break through time 60 minutes (EN 374:2004). In practice, due to variable exposure conditions, this information can only be used as an aid to selection of a suitable chemical protection glove. This information does not substitute suitability tests by the end user. A suitable glove type should be selected for each work environment. Gloves should be replaced regularly, especially after extended contact with the substance.

Eye protection: Wear approved, tightly fitting safety goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:		
Form:	Liquid	
Colour:	Colourless	
Odour:	Ester-like	
Melting Temperature:	-48ºC	
Boiling Temperature:	100.3ºC @ 1.013hPa	
Flashpoint:	10ºC (method DIN 51755 - closed cup)	
Ignition Temperature:	430ºC (method DIN 51794)	
Lower Explosion Limit:	2.1% vol. @ 10.5ºC	
Upper Explosion Limit:	12.5% vol.	
Vapour Pressure:	47hPa @ 20ºC	





Relative Density: Relative Vapour Density: Solubility in Water: Solubility (Qualitative): pH value: Partition Co-efficient: Viscosity (Dynamic): 0.94g/cm³ @ 20°C >1 @ 20°C (related to air) 1.6g/l @ 20°C, difficult to mix Miscible with most organic solvents Not applicable logPow 1.38 (measured, n-Octanol/water) 0.6mPa·s @ 20°C (method Brookfield)

Other information:

None

10. STABILITY AND REACTIVITY

Reactivity:

Refer to sections 2.3 and 10.2

Chemical stability:

Stable under normal temperature conditions and when used as directed. No decomposition occurs when used as directed.

Possibility of hazardous reactions:

Refer to section 2.3.

Conditions to avoid:

The substance is normally supplied in a stabilised form. If the permissible storage period/storage temperature is exceeded, the product may polymerise with heat generation. Avoid excessive heat for long periods of time. Avoid heat, flames and other sources of ignition.

Incompatible materials:

Free radical initiators Reducing agents Tertiary amines Heavy metals Peroxides Oxidising agents Mineral acids Strong acids/alkalis Hazardous decomposition products: Oxides of carbon. No decomposition occurs when used as directed.

11. TOXICOLOGY INFORMATION

Information on toxical acids off	Information on tovical action official			
Information on toxicological eff Metabolism:	The substance is rapidly metabolised			
Acute Oral Toxicity:	LD ₅₀ rat LD ₅₀ mouse LD ₅₀ rabbit	>5000mg/kg =5200mg/kg >5000mg/kg		
Acute Inhalation Toxicity:	LC ₅₀ rat, 4h LC ₅₀ mouse, 3h	29.8mg/l 33mg/l		
Acute Dermal Toxicity:	LD ₅₀ rabbit	>5000mg/kg		
Caustic Burning/Skin Irritation:	Rabbit, 24h (OECD 405) If skin contact is prolonged and/or frequent, irritations cannot be excluded.	Not irritating- slightly irritating		





Skin Irritant Category 2 (UN-GHS)

Serious Eye Damage/Irritation:	Rabbit, 24h	Not irritating- slightly irritating
Respiratory/Skin Sensitisation:	Guinea pig (OECD 406) Repeated exposure may cause skin dryness or cracking. In humans, variou types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affectations). Skin Irritant Category 1B (UN-GHS)	Sensitising s
Aspiration Hazard:	No evidence for hazardous properties (structure-activity relationship).	
Germ Cell Mutagenicity:	+ve as well as –ve results in <i>in vitro</i> mu /genotoxicity tests. No experimental e genotoxicity <i>in vivo</i> is available. In gene mutagenic according to international c	vidence of eral, not
Carcinogenicity:	Non-carcinogenic in inhalation and fee studies performed in rats, mice and do	-
Reprotoxicity/Teratogenicit:	No indication of toxic effects in experimed and the second s	nental
Human Health Hazard Assessment:	CMR:no	
Specific Target Organ Toxicity - single exposure:	respiratory tract irritation	Hazard Category 3
Specific Target Organ Toxicity - repeated exposure:	no evidence for hazardous properties rat, inhalation, 25-400ppm Findings: damage to nasal mucous membrane Rat, dilute ingestion, 6-2000ppm Findings: no toxic effect	NOAEL, 25ppm 400ppm NOAEL, 2000ppm
General Information:	Avoid contact with skin and eyes and in substance vapours.	nhalation of

12. ECOLOGICAL INFORMATION

Ecotoxicity:		
Aquatic Environment	Hazardous to the aquatic environment	Acute Aquatic Toxicity Category 3
Aquatoxicity, fish	LC ₅₀ Oncorhynchus mykiss, 96h LC ₅₀ Lepomis macrochirus, 72h	>79mg/l 264mg/l





	LC ₅₀ Lep	omis macrochirus, 96h		191mg/l		
Aquatoxicity, invertebrates	EC ₅₀ Daphnia magna, 48h (OECD 202) Daphnia magna, 21d flow through (OECD 202)			69mg/l NOEC, 37mg/l		
Aquatoxicity, aquatic plants	EC ₅₀ Selenastrum capricornutum, 72hr (OECD 201) EC3 Scenedesmus quadricauda, 8d (DIN 38412:9)			>110mg/l 37mg/l		
Toxicity in Microorganisms	EC3 Pseudomonas putida, 16h			100mg/l		
Persistence and degrada	bility:					
Persistence and Degradability	No evidence for hazardous properties					
Biodegradability	Readily degradable, 14d, 28d (OECD 301, 301C)94%The substance in inherently biodegradable,but not readily biodegradable to OECD criteria					
Bioaccumulative potential:						
Bioaccumulation	No evidence for hazardous properties					
Mobility in soil:						
Mobility	The substance has poor water solubility. No evidence for hazardous properties.					
Results of PBT and vPvB	assessm	nent:				
Persistent, Bioaccumulative or Toxic No (REACH, Annex VIII)						
,		No (REACH, Annex VIII)				
Other adverse effects:						
General Information		Do not allow to enter soil, waterways or waste water				

13. DISPOSAL CONSIDERATIONS

Waste treatment	methods:
Substance:	Waste is hazardous and to be treated as controlled waste. Product must be disposed of as special waste after consultation with local waste authorities and the disposal company in a suitable and licensed facility.
Packaging:	Contaminated packaging should be emptied optimally and after appropriate professional cleaning may be taken for re-use. Packaging that cannot be cleaned should be disposed of professionally. Do not puncture or incinerate, even when empty. Contaminated rags and the like must be discarded into designated a fireproof bucket.
List of Waste, LOW	Chemicals and gases in containers, 16 05
16 05 06	Laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals.
16 05 08	Discarded organic chemicals consisting of or containing dangerous substances.

SAFETY DATA SHEET



•	TRANSPORT INFORMA	TION				
	UN number:	UN 1247	Hazard Class 3, flammable liquids Packing Group II			
			3			
	UN proper shipping na					
	Land Transport ADR/GGVSE	B UN/Germany UN 1247	METHYL METHACRYLATE MONOMER MONOMER,			
			STABILISED, Class 3, Group II, Tunnel restriction code Hazard no. 339			
	Land Transport RID/GGVSEE					
		UN 1247	METHYL METHACRYLATE MONOMER MONOMER, STABILISED, Class 3, Group II Hazard no. 339			
	Inland Waterway Transport					
	ADNR/GGVSEB	UN 1247	METHYL METHACRYLATE MONOMER MONOMER, STABILISED, Class 3, Group II			
	Shipment by Sea IMDG/GGVSee	UN 1247	METHYL METHACRYLATE MONOMER MONOMER,			
		011127/	STABILISED, Class 3, Group II			
			EmS F-E, S-D			
	Air Transport ICAO/IATA		Marine pollutant No			
		UN 1247	METHYL METHACRYLATE MONOMER MONOMER, STABILISED, Class 3, Group II			
	Transport hazard class(Refer to section 14.2	es):				
	Packing group: Refer to section 14.2					
	Environmental hazards Refer to section 14.2, not ap	-	ned			
	Special precautions for user: Refer to section 14.2					
	REGULATORY INFORM	REGULATORY INFORMATION				
	Safety, health and environmental regulations/legislation specific for the substance or					
	mixture.					
	National Legislation Occupational Restrictio	ns	Note for juveniles.			
		113	Note for pregnant women and nursing mothers EC Directive 92/85/EEC			
	Status of Registration DEACH /		uncistored /suc uncistored			
	Status of Registration	RFACH (FU)	registered/bre-registered			
	Status of Registration	REACH (EU) TSCA (USA)	registered/pre-registered listed or exempt			
	Status of Registration	REACH (EU) TSCA (USA) DSL (CDN)	listed or exempt listed or exempt			
	Status of Registration	TSCA (USA)	listed or exempt			

METI (J)

listed or exempt

SAFETY DATA SHEET



		ECL (KOR) PICCS (RP) IECSC (CN) HSNO (NZ)	listed or exempt listed or exempt listed or exempt listed or exempt	Code: HSR001195
Labe	nical safety assessm Iling in accordance v toffV/EC		Methyl Methacrylate	
Haza	ard symbols	F Xi	Highly flammable Irritant	
H-sta	atements from			
Sect	ion 3	H225 H315 H317 H335	Highly flammable liquid Causes skin irritation May cause an allergic s May cause respiratory i	kin reaction
. FUF	THER INFORMATIO	N		

16. FURTHER INFORMATION

The substance is normally supplied in a stabilised form.

If the permissible storage period and/or storage temperature is noticeably exceeded, the substance may polymerise with heat evolution.

The instructions given here are valid only for the substance as supplied, not for derivatives resulting from its use.

References: Quoted manuals and standards IMO OECD-SIDS SIAR NIH NIOSH UNECE

The data given above covers exclusively the safety requirements of the product(s) and is based on our current knowledge and experience. It does not signify any warranty with regards to the products properties. This product is only supplied for specific uses in dentistry and must be used in accordance with the directions for use.